



VANDAL PROOF MINI PTZ SPEED DOME CAMERA

LE-209PTZ Series



Feature

- Smart out-look, Highly Explosion Proof
- 1/3" SONY CCD
- Pan range: 0° ~ 360° Continue (Not 355°)
- Tilt range: 0° ~ 90° Flip
- Pan Speed: Max 50° /Sec
- Preset: 16
- RS485 control, Pelco D/P Supported
- 4- 9mm dynamic varifocal lens (standard)
- 5-15mm dynamic varifocal lens (optional)

Specifications

Model	LE-209PTZC	LE-209PTZS	LE-209PTZH
Image Sensor	1/3"SONY CCD	1/3"SONY CCD	1/3"SONY CCD
Horizontal Resolution	540TV Lines Lines Low Illumination	600TV Lines Lines Low Illumination	700TV Lines Lines Low Illumination
Image	752(H) X 582(V)	795(H) X 596(V)	976(H) X 494(V)
Usable Illumination	0.001LUX/F2.0	0.001LUX/F2.0	0.001LUX/F2.0
S/N Ratio	>48dB		
Electronic Shutter Time	Auto : 1/50-1/100,000sec		
Lens	4-9mm dynamic varifocal lens (standard) / 5-15mm dynamic varifocal lens (optional)		
White Balance	Auto		
Video Output	Composite Signal (1.0Vp-p 75 Ω)		
Power Source	DC12V		
Dimension	138 x 212mm		
Weight	2.8kg		
Operation Temperature	- 10°C ~ +50°C		

Specifications and dimensions subject to change without notice.

Lifecom Technologies (HK) Co., Ltd.

Tel. : 3589 6755 Fax: 3427 3318 E-mail: info@lifecomhk.com Web-Site: www.lifecomhk.com