



OUTDOOR PTZ DOME CAMERA LE-A82X



Feature

- Attractive out look in Silver
- Pan range: 360° Continue; Tilt range: 0° ~ 90° Flip
- Manual speed pan: 0.1 - 300° /S; Tilt: 0.1 ~ 120° /S
- Preset point: 128; speed: 400° /S; accuracy: $\pm 0.10^\circ$
- IP66; Build in heater, Working in: - 220°C ~ 60 °C
- Intelligent power off real time memory
- Auto Scan; High efficient 3-dimension scan
- Continue Manual
- Size: $\phi 214 \times 238$ (288 with bracket)

Specifications

Model	LE-A82X
Basic Features	Operation crosshair function Pan and tilt position display High efficient 3-dimension scan Log-focus speed-limited Intelligent power off real time memory Home position Camera menu operation Endless manual operation
Pan/Tilt Range	Pan: 360° Continue; Tilt: 0° ~ 90° Flip
Manual Speed Pan/Tilt	Pan: 0.1 ~ 300° /Sec; Tilt: 0.1 ~ 120° /Sec
Preset	Speed: 400° /Sec; Accuracy: $\pm 0.10^\circ$; Points: 128
Privacy Zones (Masking)	8 Programmable zones
Sector Label Display	8 Programmable zones
PTZ Tours (Pattern)	3 Programmable (Pan/Tilt/Zoom and each tour is 120 seconds)
Vector Scan Groups	6 Programmable (Dwell time speed preset point and embed other vector scan or PTZ tours)
Auto Scan	With Smart Programmable variable speed
IP66 for Outdoor Use	YES
Power	24VAC 2A 60Hz/50Hz
Communication	RS485 (+ / -)
Connection	BNC cable

Specifications and dimensions subject to change without notice.

Lifecom Technologies (HK) Co., Ltd.

Tel. : 3589 6755 Fax: 3427 3318 E-mail: info@lifecomhk.com Web-Site: www.lifecomhk.com