

# Intrusion alarm controller - LE-IRC239



Specifications	LE-IRC239
Alarm Communications	Transmitting alarming signal by PSTN dialing
Number of zones	8 wire + 8 wireless zones
Programming mode	Local keyboard Program, Extension keypad program, Remote program and timer
Alarm response time	200~800ms
Memory capability of alarming telephone numbers	More the 5groups of alarming telephone numbers
Arming / disarming mode	By remote control unit, keypad, long-distance telephone remote control and timer
Data memory for inquiry	1 record for power-on time, 10 for arming/disarming times, 14 for alarm information
Voice recording	90s
Wireless receipt	315M (433M optional) and learning of code checking
Alarm linked output	NO/NC. load:1A 120VAC/24VDC
Output of power supply (capable of turn-off)	DC12V 500mA
Power supply of alarming	DC12V 500mA
Max output power capacity	DC12V 1000mA
Applicable temp. / humidity	-10℃ ~ 55℃ / <90%
Power supply	AC220V±10%, 50Hz
Spare power supply	DC 12V 7Ah maintenance-free accumulator
Installation style	Wall-hanging or embedded
Material of casing	High-quality steel plate
Dimensions (L/W/H)	264 x 80 x 261
Weight (plus battery)	Approx, 3.42kg (Approx, 5.58kg)