



IP CAMERA

LE-P176

Feature:

- ◆ Motion-JPEG video compression format, CMOS 0.3 megapixel
- ◆ Support 32G SD card local memory
- ◆ Support WIFI, IEEE802.11b/g/n
- ◆ Mobile view allow you remote viewing & record from anywhere anytime
- ◆ Pan/Tilt control (Pan: 270° & Tilt: 90°)
- ◆ Built-in IR-CUT, made video more real and clear day and night
- ◆ Two-way audio monitoring
- ◆ IR night vision 20m



Specifications		MODEL: LE-R176
Video	Compression	MJPE
	Signal system	CMOS 300,000pixels
	Frame rate	30fps
	Shutter speed	1/50s-1/100,000s
	resolution	VGA(640*480), QVGA(320*240) QQVGA (160*120)
	Video adjustment	brightness, contrast, chrome, saturation.
	WB, BLC	Auto
Night vision	Filter switch	Built-in IR Cut, filter switch automatically, without color cast
	Night vision	10 Φ5 LED lights IR distance: 20m
Audio	Compression	G.726/G.711 built-in two-way audio processor, support sound monitor
	Audio Gain	AGC
P/T	Motor	Built-in motor control
	Rotation angle	Horizontal: 270° Vertical: 90°
Network	Network interface	RJ-45 10/100M self-adaptable Ethernet slot
	Protocol	Support TCP、IP、UDP、HTTP、SMTP、FTP、DHCP、NTP、DDNS、uPnP、PPPoE、TFTP、ARP、RTSP etc.
	Wireless	802.11b/g/n, wireless automatically search and set
	Online visitor	Support 15 visitors at the same time
	IP mode	Dynamic IP address, static IP address, PPPOE
Others	Power	DC5V 2A
	Temperature	-10~80 °C
	Humidity	95% RH
	Size	118*105*120mm (L*W*H)
Alarm	Input/output	1/1
	Alarm detection	Motion detection
	Alarm action	Support e-mail, FTP server, ringtones alarm, PTZ preset alarm etc.
System requirement		Microsoft Win98 SE/ME/2000/XP, Vista IE 6.0, NET4.5, firefox, chrome

Specifications and dimensions subject to change without notice.

Lifecom Technologies (HK) Co., Ltd.

Tel. : 3589 6755 Fax: 3427 3318 E-mail: info@lifecomhk.com Web-Site: www.lifecomhk.com