



Megapixel HD CAMERA

LE-P7 Series HD Indoor Camera
1.3M / 2M / 3M / 4M



Feature:

- ◆ With IR LED
- ◆ Dual bit rate: Record in 2034x1728 locally and CIF remotely (max)
- ◆ Audio in optional
- ◆ POE (Power over Ethernet) in optional
- ◆ Automatic exposure and white balance
- ◆ Up and down angle adjustable
- ◆ Firmware and software updatable
- ◆ Free DDNS

| Model No. | LE-P7130 | LE-P7200 | LE-P7300 | LE-P7400 |
|----------------------------|---|--------------------|--------------------|------------------|
| Image sensor | 1/3" CMOS Sensor | 1/2.7" CMOS Sensor | 1/2.9" CMOS Sensor | 1/3" CMOS Sensor |
| Pixel | 1.3M (Color) | 2M (Color) | 3M (Color) | 4M (Color) |
| Video compression | MPEG-4/H.264 | | | |
| Preview resolution | 1280x720 | 1920x1080 | 2048 x 1536 | 2304 x 1728 |
| Exposure mode | Automatic exposure and white balance | | | |
| Lens | 3.6 /6 /8 /10 mm in Optional | | | |
| Min. illumination | 0.2Lux (IR led on) | | | |
| Tilt range | to 55° adjustable by manual | | | |
| Focus | Manual | | | |
| Video frame rate | 30 fps | | | 20 fps |
| Video compression bit rate | 500K - 3Mbps | | | |
| Protocol | TCP/UDP/IP/HTTP/FTP/SMTP/DHCP/DNS/ARP/ICMP/POP3/NTP | | | |
| Communication interface | RJ45, 100M Self-adaptive Ethernet Interface | | | |
| Power input | DC 12V 1A | | | |
| Back-end equipments | DVR cards / Hybrid DVR / PDVR / PC | | | |
| Power consumption | Max. 6W | | | |
| Working / Storage temp. | -10 ~ +45 °C / -20 ~ +70 °C | | | |
| Working humidity / O/S | 10 ~ 95% / Linux | | | |
| Dimension / Weight | 94 x 69 (H) mm / 450g | | | |

Specifications and dimensions subject to change without notice.

Lifecom Technologies (HK) Co., Ltd.

Tel. : 3589 6755 Fax: 3427 3318 E-mail: info@lifecomhk.com Web-Site: www.lifecomhk.com