LE-R8204 / LE-R8208 / LE-R8216 H.264, 4CH / 8CH / 16CH DVR)



Digital Security System

PERFORMANCE & RELIABILITY

H.264





Feature:

- H.264 Baseline: 9 selectable video quality levels
- Hexaplex operation simultaneous record, live, playback, backup, control & remote access
- Mixed operation windows playback video and live monitoring in one screen
- Recording quality can be configured in two groups better usage of hard disk
- Multi-level password to ensure high degree of security
- Playback search by time or event (alarm, motion & video loss)
- Support mobile phone, WAP protocol
- 50nos of IP address preset
- 36 camera in one screen
- Multi place link-up



N. JAN ELEMENTON SVR.	A Jos Brandson Dill. N	200 Researched DVR 10200 E	0.00474	•
N.301 Entirekted DVR			mental (1986	0
N. (See Enterested See			matted (Ink	
N. Jid Begrested DVR	A JOS Dissolution N	201 Street Str. 10.201 St.	entire (100	



LE-R8204 / LE-R8208 / LE-R8216 (H 264, 4CH / 8CH / 16CH DVR)



FUNCTIONAL SPECIFICATIONS

Description		Specification				
		LE-R8204	LE-R8208	LE-R8216		
Video -	Video Input	4 Channels	8 Channels	16 Channels		
	video iriput	Independent Input with 1.0Vp-p,75 Ω BNC				
	Video Output	1ch PAL/NTSC Output with 1.0Vp-p, 75 Ω BNC, Composite Video Signal				
	Video Odiput	1ch VGA Display Output				
Audio	Audio Input/Output	4ch Input	8ch Input	16ch Input		
	riadio inpat o atpat	1ch output				
Digital Processing and Storing	Compression	H.264 Baseline				
	Audio	ADPCM				
	Storage	Over 500G bytes, SATA				
Record	Recording Time	7~20days with 500GB HD @25fps for continuous recording mode				
	Recording Mode	Continuous, motion detection, sensor activated, time schedule				
Resolution -	Display	NTSC: 704X480, PAL:704X576				
	Recording	NTSC: 30/704x480 PAL: 25/704x576				
Sensors, Alarm	Output	1 Output	2 Output			
Frame rate	Recording (FPS)	100(704X576) FPS	200(704X576) FPS			
Network	Network interface	1 RJ-45 10/100Mdps Ethernet connector				
PTZ	Pan/Tilt/Zoom	RS-485				
Archiving	Back-up	1 USB 2.0 ports for USB 2.0 flash disk, DVD±RW, DVD±R, Card readers, HDD, etc.				
F/W upgrade	Network / USB2.0	Firmware Upgrade via USB, network				
Other	Power	12VDC, 4A	12VDC, 6A			
	Working Temperature		0~+50°C			
	Dimensions	325x224x52mm	430x370x97mm	430x370x97mm		

The above specification can be changed without previous notice for improvement of product.

Lifecom Technologies (HK) Co., Ltd.

Tel.: 3589 6755 Fax: 3427 3318 E-mail: info@lifecomhk.com Web-Site: www.lifecomhk.com