



Weatherproof IR Camera LE-W50 Series



Feature

- Attractive outlook
- 1/3" SONY CCD
- Water Resistance : IP66
- Built-in bracket, 3-Axis direction bracket
- Lens: 4-9mm Manual Zoom lens
- IR LED: ϕ 8X36PCS ,IR Distance:50M
- Others function : AWB

Specifications

Model	LE-W50T	LE-W50C	LE-W50HD
Signal System	PAL		
Image Sensor	1/3"SONY CCD		
Horizontal Resolution	480TV Lines	540TV Lines	700TV Lines
Image	582(H) X500(V)	752(H) X582(V)	976(H) X 494(V)
Usable Illumination	0 Lux/F2.0 (LED ON)		
S/N Ratio	>48dB (AGC OFF)		
Len	4-9mm Manual Zoom lens		
Synchronization System	Internal		
Video Output	1.0Vp-p 75 Ω BNC		
IR Power On	CDS Auto Control		
IR LED	ϕ 8 X 36 PCS		
IR series Distance	About 45m		
IR Status	Under 10 Lux By CDS		
Power supply	DC12V 300mA		
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max		
Dimension	151(W) x101(H) x 95(D)mm		
Net Weight	1500g		

Specifications and dimensions subject to change without notice.

Lifecom Technologies (HK) Co., Ltd.

Tel. : 3589 6755 Fax: 3427 3318 E-mail: info@lifecomhk.com Web-Site: www.lifecomhk.com